

STRIP  
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: July

With process factor valid for finished cold rolled and hardened and tempered strip products

Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

GRADE			ALLOY & ENERGY SURCHARGE PER KG										
Sandvik	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD
<b>Alloyed non-stainless steels and carbon steels</b>													
15LM	1.1248	1074	1770	8,13	0,77	0,66	0,82	106,96	1,05	5,51	0,80	0,37	0,48
20C	1.1274	1095	1870	8,28	0,79	0,67	0,84	108,86	1,07	5,61	0,82	0,38	0,48
20C2			2258	9,20	0,88	0,75	0,93	120,97	1,19	6,23	0,91	0,42	0,54
25C				8,25	0,78	0,67	0,83	108,46	1,06	5,59	0,81	0,38	0,48
10C16Mo3V1				21,75	2,07	1,76	2,20	285,96	2,80	14,73	2,14	1,00	1,27
Sanprint XP				19,24	1,83	1,56	1,94	252,99	2,48	13,03	1,90	0,88	1,12
****													
<b>Martensitic stainless chromium steels</b>													
6C27	1.4007	420	2234	18,52	1,76	1,50	1,87	243,58	2,39	12,55	1,82	0,85	1,08
7C27Mo2				23,78	2,26	1,93	2,40	312,74	3,06	16,11	2,34	1,09	1,39
10C28MO2				24,16	2,30	1,96	2,44	317,75	3,11	16,37	2,38	1,11	1,41
12C27M				19,13	1,82	1,55	1,93	251,59	2,47	12,96	1,88	0,88	1,12
12C27				18,41	1,75	1,49	1,86	242,08	2,37	12,47	1,81	0,84	1,08
14C28N				18,75	1,78	1,52	1,90	246,58	2,42	12,70	1,85	0,86	1,10
13C26				17,95	1,71	1,46	1,81	236,07	2,31	12,16	1,77	0,82	1,05
19C27				18,41	1,75	1,49	1,86	242,08	2,37	12,47	1,81	0,84	1,08
****													
<b>Austenitic stainless steels</b>													
12R11	1.4310	301	2331	45,68	4,35	3,70	4,62	600,67	5,89	30,94	4,50	2,09	2,67
11R51	1.4310	301	2231	48,91	4,65	3,97	4,94	643,13	6,30	33,12	4,82	2,24	2,86
13RM19	EN 1.4369			46,49	4,42	3,77	4,70	611,25	5,99	31,48	4,58	2,13	2,72
316LVM	1,4441	316LVM		84,29	8,02	6,84	8,52	1 108,37	10,86	57,09	8,30	3,86	4,93
2RK65HV				126,35	12,02	10,25	12,77	1 661,36	16,28	85,57	12,45	5,79	7,38
3X8R65				66,56	6,33	5,40	6,73	875,17	8,57	45,08	6,56	3,05	3,89
****													
<b>Precipitation hardenable steels</b>													
9RU10	1.4568	631	2388	46,22	4,40	3,75	4,67	607,75	5,95	31,30	4,55	2,12	2,70
NANOFLEX				69,27	6,59	5,62	7,00	910,85	8,92	46,91	6,82	3,18	4,05
1RK95				45,20	4,30	3,67	4,57	594,38	5,82	30,61	4,45	2,07	2,64
****													
<b>Duplex stainless steels (austenitic-ferritic)</b>													
SAF2205	EN 1.4462		2377	60,77	5,78	4,93	6,14	799,06	7,83	41,16	5,99	2,79	3,55
SAF2507	EN 1.4410		2328	70,84	6,74	5,75	7,16	931,53	9,13	47,98	6,98	3,25	4,14
SAF3207HD				73,59	7,00	5,97	7,44	967,64	9,48	49,84	7,25	3,37	4,30
****													
<b>Ferritic stainless chromium steel</b>													
1C429				26,02	2,48	2,11	2,63	342,17	3,35	17,62	2,56	1,19	1,52
1C44Mo20				30,25	2,88	2,45	3,06	397,82	3,90	20,49	2,98	1,39	1,77
0XC34				21,07	2,01	1,71	2,13	277,11	2,72	14,27	2,08	0,97	1,23
1C34				20,92	1,99	1,70	2,11	275,11	2,70	14,17	2,06	0,96	1,22
****													
<b>Nickel-base alloy</b>													
SANICRO75X2	UNS N07750			263,01	25,03	21,33	26,58	3 458,40	33,88	178,13	25,91	12,06	15,37
SAN62TiNb				229,30	21,82	18,60	23,18	3 015,17	29,54	155,30	22,59	10,51	13,40
****													
<b>Energy surcharge per kg included in total surcharge</b>				3,43	0,33	0,28	0,35	45,06	0,44	2,32	0,34	0,16	0,20