

STRIP  
ALLOY & ENERGY SURCHARGE

**VALID FOR INVOICING: October**

With process factor valid for finished cold rolled and hardened and tempered strip products

Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

GRADE			ALLOY & ENERGY SURCHARGE PER KG										
Alleima	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD
<b>Alloyed non-stainless steels and carbon steels</b>													
15LM	1.1248	1074	1770	9,87	0,93	0,79	0,93	129	1,21	6,40	0,90	0,42	0,55
20C	1.1274	1095	1870	9,98	0,94	0,80	0,94	131	1,22	6,47	0,91	0,43	0,56
20C2			2258	10,71	1,01	0,86	1,01	140	1,31	6,94	0,97	0,46	0,60
25C				9,96	0,94	0,80	0,94	130	1,22	6,45	0,90	0,42	0,55
10C16Mo3V1				21,70	2,04	1,74	2,04	284	2,66	14,07	1,97	0,93	1,21
Sanprint XP				19,80	1,86	1,59	1,86	259	2,43	12,83	1,80	0,84	1,10
****													
<b>Martensitic stainless chromium steels</b>													
6C27	1.4007	420	2234	18,08	1,70	1,45	1,70	237	2,22	11,72	1,64	0,77	1,01
7C27Mo2				23,01	2,16	1,85	2,16	301	2,82	14,91	2,09	0,98	1,28
Hiflex				23,01	2,16	1,85	2,16	301	2,82	14,91	2,09	0,98	1,28
Freeflex				23,88	2,24	1,92	2,25	313	2,93	15,48	2,17	1,02	1,33
10C28MO2				23,31	2,19	1,87	2,19	305	2,86	15,11	2,12	0,99	1,30
12C27M				18,56	1,74	1,49	1,75	243	2,28	12,03	1,69	0,79	1,03
12C27				17,99	1,69	1,45	1,69	236	2,21	11,66	1,63	0,77	1,00
14C28N				18,26	1,71	1,47	1,72	239	2,24	11,84	1,66	0,78	1,02
13C26				17,63	1,66	1,42	1,66	231	2,16	11,43	1,60	0,75	0,98
19C27				17,99	1,69	1,45	1,69	236	2,21	11,66	1,63	0,77	1,00
****													
<b>Austenitic stainless steels</b>													
12R11	1.4310	301	2331	40,14	3,77	3,23	3,78	526	4,93	26,02	3,65	1,71	2,23
11R51	1.4310	301	2231	43,23	4,06	3,47	4,07	567	5,31	28,03	3,93	1,84	2,41
13RM19	EN 1.4369			40,77	3,83	3,28	3,84	534	5,00	26,43	3,71	1,74	2,27
316LVM	1.4441	316LVM		73,39	6,89	5,90	6,90	962	9,01	47,57	6,67	3,13	4,08
2RK65HV				108,43	10,18	8,71	10,20	1 421	13,31	70,29	9,85	4,63	6,04
3X8R65				58,49	5,49	4,70	5,50	766	7,18	37,92	5,32	2,50	3,26
****													
<b>Precipitation hardenable steels</b>													
9RU10	1.4568	631	2388	40,59	3,81	3,26	3,82	532	4,98	26,31	3,69	1,73	2,26
NANOFLEX				63,65	5,98	5,12	5,99	834	7,81	41,26	5,78	2,72	3,54
1RK95				39,86	3,74	3,20	3,75	522	4,89	25,84	3,62	1,70	2,22
****													
<b>Duplex stainless steels (austenitic-ferritic)</b>													
SAF2205	EN 1.4462		2377	54,38	5,11	4,37	5,12	713	6,67	35,25	4,94	2,32	3,03
SAF2507	EN 1.4410		2328	62,93	5,91	5,06	5,92	825	7,72	40,79	5,72	2,69	3,50
SAF3207HD				64,77	6,08	5,21	6,09	849	7,95	41,99	5,89	2,76	3,61
****													
<b>Ferritic stainless chromium steel</b>													
1C429				24,00	2,25	1,93	2,26	315	2,95	15,56	2,18	1,02	1,34
1C44Mo20				28,12	2,64	2,26	2,65	368	3,45	18,23	2,56	1,20	1,57
0XC34				20,09	1,89	1,61	1,89	263	2,47	13,03	1,83	0,86	1,12
1C34				19,97	1,88	1,61	1,88	262	2,45	12,95	1,82	0,85	1,11
****													
<b>Nickel-base alloy</b>													
SANICRO75X2	UNS N07750			217,25	20,40	17,46	20,44	2 847	26,66	140,83	19,74	9,27	12,09
SAN62TiNb				189,78	17,82	15,25	17,85	2 487	23,29	123,02	17,25	8,10	10,56
****													
<b>Energy surcharge per kg included in total surcharge</b>				5,74	0,54	0,46	0,54	75	0,70	3,72	0,52	0,24	0,32