

STRIP
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: **November**

With process factor valid for finished cold rolled and hardened and tempered strip products

Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

GRADE			ALLOY & ENERGY SURCHARGE PER KG										
Alleima	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD
Alloyed non-stainless steels and carbon steels													
15LM	1.1248	1074	1770	10,72	0,98	0,87	0,96	139	1,31	6,86	0,95	0,44	0,60
20C	1.1274	1095	1870	10,84	0,99	0,87	0,97	141	1,33	6,94	0,96	0,44	0,60
20C2			2258	11,57	1,06	0,93	1,04	151	1,42	7,41	1,02	0,47	0,64
25C				10,81	0,99	0,87	0,97	141	1,32	6,92	0,96	0,44	0,60
10C16Mo3V1				24,21	2,22	1,95	2,18	315	2,96	15,50	2,14	0,99	1,34
Sanprint XP				22,41	2,06	1,81	2,01	292	2,74	14,35	1,98	0,91	1,24

Martensitic stainless chromium steels													
6C27	1.4007	420	2234	18,99	1,74	1,53	1,71	247	2,32	12,16	1,68	0,77	1,05
7C27Mo2				25,08	2,30	2,02	2,26	326	3,07	16,06	2,22	1,02	1,39
Hiflex				25,08	2,30	2,02	2,26	326	3,07	16,06	2,22	1,02	1,39
Freeflex				25,94	2,38	2,09	2,33	338	3,18	16,61	2,29	1,06	1,44
10C28MO2				25,38	2,33	2,05	2,28	330	3,11	16,25	2,24	1,04	1,41
12C27M				19,48	1,79	1,57	1,75	253	2,38	12,47	1,72	0,79	1,08
12C27				18,90	1,73	1,53	1,70	246	2,31	12,10	1,67	0,77	1,05
14C28N				19,18	1,76	1,55	1,72	250	2,35	12,28	1,70	0,78	1,06
13C26				18,54	1,70	1,50	1,67	241	2,27	11,87	1,64	0,76	1,03
19C27				18,90	1,73	1,53	1,70	246	2,31	12,10	1,67	0,77	1,05

Austenitic stainless steels													
12R11	1.4310	301	2331	42,97	3,94	3,47	3,86	559	5,26	27,51	3,80	1,75	2,39
11R51	1.4310	301	2231	46,87	4,30	3,78	4,21	610	5,74	30,01	4,14	1,91	2,60
13RM19	EN 1.4369			43,58	4,00	3,52	3,92	567	5,33	27,90	3,85	1,78	2,42
316LVM	1,4441	316LVM		81,24	7,46	6,56	7,31	1 057	9,94	52,02	7,18	3,31	4,51
2RK65HV				120,36	11,04	9,72	10,82	1 566	14,73	77,06	10,64	4,91	6,68
3X8R65				64,48	5,92	5,21	5,80	839	7,89	41,28	5,70	2,63	3,58

Precipitation hardenable steels													
9RU10	1.4568	631	2388	43,48	3,99	3,51	3,91	566	5,32	27,84	3,84	1,77	2,41
NANOFLEX				71,51	6,56	5,77	6,43	930	8,75	45,79	6,32	2,92	3,97
1RK95				42,94	3,94	3,47	3,86	559	5,26	27,50	3,80	1,75	2,38

Duplex stainless steels (austenitic-ferritic)													
SAF2205	EN 1.4462		2377	60,47	5,55	4,88	5,44	787	7,40	38,72	5,35	2,47	3,36
SAF2507	EN 1.4410		2328	70,08	6,43	5,66	6,30	912	8,58	44,87	6,20	2,86	3,89
SAF3207HD				71,48	6,56	5,77	6,43	930	8,75	45,77	6,32	2,92	3,97

Ferritic stainless chromium steel													
1C429				24,96	2,29	2,02	2,24	325	3,06	15,98	2,21	1,02	1,39
1C44Mo20				30,23	2,77	2,44	2,72	393	3,70	19,35	2,67	1,23	1,68
0XC34				21,02	1,93	1,70	1,89	274	2,57	13,46	1,86	0,86	1,17
1C34				20,90	1,92	1,69	1,88	272	2,56	13,38	1,85	0,85	1,16

Nickel-base alloy													
SANICRO75X2	UNS N07750			236,88	21,74	19,12	21,30	3 082	28,99	151,66	20,94	9,66	13,15
SAN62TiNb				206,81	18,98	16,70	18,60	2 691	25,31	132,42	18,29	8,44	11,48

Energy surcharge per kg included in total surcharge				6,84	0,63	0,55	0,62	89	0,84	4,38	0,60	0,28	0,38