

STRIP  
ALLOY & ENERGY SURCHARGE

**VALID FOR INVOICING: December**

With process factor valid for finished cold rolled and hardened and tempered strip products

Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

GRADE			ALLOY & ENERGY SURCHARGE PER KG										
Alleima	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD
<b>Alloyed non-stainless steels and carbon steels</b>													
15LM	1.1248	1074	1770	7,92	0,73	0,63	0,72	106	0,98	5,22	0,72	0,33	0,45
20C	1.1274	1095	1870	8,03	0,74	0,64	0,73	107	0,99	5,29	0,73	0,33	0,45
20C2			2258	8,71	0,80	0,69	0,79	117	1,08	5,74	0,79	0,36	0,49
25C				8,01	0,73	0,64	0,73	107	0,99	5,27	0,72	0,33	0,45
10C16Mo3V1				21,53	1,97	1,72	1,96	288	2,67	14,17	1,94	0,89	1,21
Sanprint XP				19,91	1,82	1,59	1,81	266	2,47	13,11	1,80	0,82	1,12
****													
<b>Martensitic stainless chromium steels</b>													
6C27	1.4007	420	2234	15,64	1,43	1,25	1,43	209	1,94	10,30	1,41	0,65	0,88
7C27Mo2				22,04	2,02	1,76	2,01	295	2,73	14,52	1,99	0,91	1,24
Hiflex				22,04	2,02	1,76	2,01	295	2,73	14,52	1,99	0,91	1,24
Freeflex				22,90	2,10	1,83	2,09	307	2,84	15,08	2,07	0,95	1,29
10C28MO2				22,32	2,05	1,78	2,03	299	2,77	14,70	2,02	0,92	1,25
12C27M				16,09	1,47	1,28	1,47	215	1,99	10,60	1,45	0,67	0,90
12C27				15,56	1,43	1,24	1,42	208	1,93	10,24	1,40	0,64	0,87
14C28N				15,81	1,45	1,26	1,44	212	1,96	10,41	1,43	0,65	0,89
13C26				15,22	1,39	1,21	1,39	204	1,89	10,02	1,37	0,63	0,86
19C27				15,56	1,43	1,24	1,42	208	1,93	10,24	1,40	0,64	0,87
****													
<b>Austenitic stainless steels</b>													
12R11	1.4310	301	2331	39,88	3,65	3,18	3,63	534	4,94	26,26	3,60	1,65	2,24
11R51	1.4310	301	2231	44,03	4,03	3,51	4,01	589	5,45	28,99	3,98	1,82	2,47
13RM19	EN 1.4369			40,43	3,70	3,22	3,68	541	5,01	26,62	3,65	1,67	2,27
316LVM	1.4441	316LVM		79,39	7,27	6,33	7,23	1 062	9,84	52,28	7,17	3,28	4,46
2RK65HV				119,37	10,94	9,51	10,88	1 598	14,79	78,61	10,78	4,93	6,71
3X8R65				62,19	5,70	4,96	5,67	832	7,70	40,95	5,62	2,57	3,49
****													
<b>Precipitation hardenable steels</b>													
9RU10	1.4568	631	2388	40,42	3,70	3,22	3,68	541	5,01	26,62	3,65	1,67	2,27
NANOFLEX				70,01	6,41	5,58	6,38	937	8,67	46,10	6,32	2,89	3,93
1RK95				40,14	3,68	3,20	3,66	537	4,97	26,43	3,62	1,66	2,26
****													
<b>Duplex stainless steels (austenitic-ferritic)</b>													
SAF2205	EN 1.4462		2377	58,07	5,32	4,63	5,29	777	7,19	38,24	5,24	2,40	3,26
SAF2507	EN 1.4410		2328	67,83	6,21	5,41	6,18	908	8,40	44,67	6,13	2,80	3,81
SAF3207HD				68,85	6,31	5,49	6,27	921	8,53	45,34	6,22	2,85	3,87
****													
<b>Ferritic stainless chromium steel</b>													
1C429				21,21	1,94	1,69	1,93	284	2,63	13,97	1,92	0,88	1,19
1C44Mo20				26,85	2,46	2,14	2,45	359	3,33	17,68	2,42	1,11	1,51
0XC34				17,54	1,61	1,40	1,60	235	2,17	11,55	1,58	0,72	0,99
1C34				17,42	1,60	1,39	1,59	233	2,16	11,47	1,57	0,72	0,98
****													
<b>Nickel-base alloy</b>													
SANICRO75X2	UNS N07750			237,38	21,75	18,92	21,63	3 177	29,41	156,32	21,44	9,81	13,34
SAN62TiNb				206,77	18,94	16,48	18,84	2 767	25,62	136,16	18,67	8,55	11,62
****													
<b>Energy surcharge per kg included in total surcharge</b>				4,05	0,37	0,32	0,37	54	0,50	2,67	0,37	0,17	0,23