

STRIP
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: January

With process factor valid for finished cold rolled and hardened and tempered strip products
Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

Alleima	GRADE		ALLOY & ENERGY SURCHARGE PER KG											
	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD	BRL
Alloyed non-stainless steels and carbon steels														
20C	1.1274	1095	1870	7,47	0,66	0,57	0,71	105	0,97	5,12	0,63	0,32	0,44	3,51
20C2			2258	7,97	0,70	0,61	0,76	112	1,04	5,47	0,67	0,35	0,47	3,74
10C16Mo3V1				18,48	1,63	1,41	1,77	261	2,41	12,67	1,55	0,80	1,09	8,68
Sanprint XP				17,37	1,53	1,32	1,66	245	2,26	11,91	1,46	0,75	1,03	8,16

Martensitic stainless chromium steels														
6C27	1.4007	420	2234	13,08	1,15	1,00	1,25	184	1,70	8,96	1,10	0,57	0,77	6,14
7C27Mo2				18,56	1,63	1,41	1,78	262	2,42	12,72	1,56	0,81	1,10	8,71
Hiflex				18,56	1,63	1,41	1,78	262	2,42	12,72	1,56	0,81	1,10	8,71
Freeflex				19,38	1,71	1,48	1,86	273	2,53	13,29	1,63	0,84	1,15	9,10
10C28MO2				18,77	1,65	1,43	1,80	265	2,44	12,86	1,58	0,81	1,11	8,81
12C27M				13,41	1,18	1,02	1,28	189	1,75	9,19	1,13	0,58	0,79	6,30
12C27				13,01	1,15	0,99	1,25	184	1,70	8,92	1,09	0,57	0,77	6,11
14C28N				13,20	1,16	1,01	1,26	186	1,72	9,05	1,11	0,57	0,78	6,20
13C26			14141	12,76	1,12	0,97	1,22	180	1,66	8,75	1,07	0,55	0,75	5,99
Damax				15,79	1,39	1,20	1,51	223	2,06	10,82	1,33	0,69	0,93	7,41
19C27				13,01	1,15	0,99	1,25	184	1,70	8,92	1,09	0,57	0,77	6,11

Austenitic stainless steels														
12R11	1.4310	301	2331	27,89	2,45	2,12	2,67	393	3,63	19,11	2,35	1,21	1,65	13,09
11R51	1.4310	301	2231	31,47	2,77	2,40	3,01	444	4,10	21,57	2,65	1,37	1,86	14,78
13RM19	EN 1.4369			28,33	2,49	2,16	2,71	400	3,69	19,42	2,38	1,23	1,67	13,30
316LVM	1,4441	316LVM		56,25	4,95	4,28	5,38	793	7,33	38,55	4,73	2,44	3,32	26,41
2RK65HV				82,49	7,26	6,28	7,90	1 164	10,75	56,54	6,94	3,58	4,88	38,73
3X8R65				44,75	3,94	3,41	4,28	631	5,83	30,67	3,76	1,94	2,64	21,01
3R60F1				54,72	4,82	4,17	5,24	772	7,13	37,51	4,60	2,38	3,23	25,69

Precipitation hardenable steels														
9RU10	1.4568	631	2388	28,18	2,48	2,15	2,70	397	3,67	19,31	2,37	1,22	1,67	13,23
NANOFLEX				52,95	4,66	4,03	5,07	747	6,90	36,29	4,45	2,30	3,13	24,86
1RK95				27,61	2,43	2,10	2,64	390	3,60	18,93	2,32	1,20	1,63	12,97

Duplex stainless steels (austenitic-ferritic)														
SAF2205	EN 1.4462		2377	44,48	3,92	3,39	4,26	627	5,80	30,49	3,74	1,93	2,63	20,88
SAF2507	EN 1.4410		2328	51,54	4,54	3,92	4,93	727	6,72	35,33	4,34	2,24	3,05	24,20
SAF3207HD				51,93	4,57	3,95	4,97	732	6,77	35,59	4,37	2,25	3,07	24,38

Ferritic stainless chromium steel														
1C429				17,18	1,51	1,31	1,64	242	2,24	11,78	1,45	0,75	1,02	8,07
1C44Mo20				22,10	1,95	1,68	2,12	312	2,88	15,15	1,86	0,96	1,31	10,38
0XC34				14,47	1,27	1,10	1,39	204	1,89	9,92	1,22	0,63	0,86	6,80
1C34				14,39	1,27	1,10	1,38	203	1,87	9,86	1,21	0,62	0,85	6,76

Nickel-base alloy														
SANICRO75X2	UNS N07750			146,34	12,88	11,14	14,01	2 064	19,07	100,31	12,31	6,35	8,65	68,71
SAN62TiNb				127,97	11,26	9,74	12,25	1 805	16,67	87,72	10,76	5,56	7,56	60,08

Energy surcharge per kg included in total surcharge				3,10	0,27	0,24	0,30	44	0,40	2,12	0,26	0,13	0,18	1,45