

STRIP  
ALLOY & ENERGY SURCHARGE

**VALID FOR INVOICING: April**

With process factor valid for finished cold rolled and hardened and tempered strip products  
Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

Alleima	GRADE		ALLOY & ENERGY SURCHARGE PER KG											
	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD	BRL
<b>Alloyed non-stainless steels and carbon steels</b>														
20C	1.1274	1095	1870	6,65	0,59	0,51	0,64	96	0,87	4,63	0,57	0,29	0,39	3,20
20C2			2258	7,14	0,64	0,55	0,69	103	0,94	4,98	0,61	0,31	0,42	3,43
10C16Mo3V1				18,80	1,68	1,43	1,82	272	2,46	13,10	1,60	0,83	1,12	9,04
Sanprint XP				17,81	1,59	1,36	1,73	258	2,33	12,41	1,52	0,78	1,06	8,56
****														
<b>Martensitic stainless chromium steels</b>														
6C27	1.4007	420	2234	12,14	1,08	0,93	1,18	176	1,59	8,46	1,04	0,53	0,72	5,84
7C27Mo2				18,48	1,65	1,41	1,79	267	2,42	12,88	1,58	0,81	1,10	8,88
Hiflex				18,48	1,65	1,41	1,79	267	2,42	12,88	1,58	0,81	1,10	8,88
Freeflex				19,32	1,72	1,47	1,87	280	2,53	13,46	1,65	0,85	1,15	9,29
10C28MO2				18,69	1,67	1,43	1,81	270	2,45	13,02	1,59	0,82	1,11	8,98
12C27M				12,46	1,11	0,95	1,21	180	1,63	8,69	1,06	0,55	0,74	5,99
12C27				12,08	1,08	0,92	1,17	175	1,58	8,42	1,03	0,53	0,72	5,81
14C28N				12,26	1,09	0,94	1,19	177	1,60	8,54	1,05	0,54	0,73	5,89
13C26			14141	11,83	1,06	0,90	1,15	171	1,55	8,25	1,01	0,52	0,70	5,69
Damax				15,28	1,36	1,17	1,48	221	2,00	10,65	1,30	0,67	0,91	7,34
19C27				12,08	1,08	0,92	1,17	175	1,58	8,42	1,03	0,53	0,72	5,81
****														
<b>Austenitic stainless steels</b>														
12R11	1.4310	301	2331	27,76	2,48	2,12	2,69	402	3,63	19,35	2,37	1,22	1,65	13,35
11R51	1.4310	301	2231	31,96	2,85	2,44	3,10	462	4,18	22,27	2,73	1,40	1,90	15,36
13RM19	EN 1.4369			28,18	2,51	2,15	2,73	408	3,69	19,64	2,40	1,24	1,67	13,55
316LVM	1,4441	316LVM		59,34	5,29	4,53	5,75	859	7,77	41,35	5,06	2,61	3,52	28,52
2RK65HV				87,82	7,84	6,70	8,51	1 271	11,50	61,20	7,49	3,86	5,21	42,21
3X8R65				46,76	4,17	3,57	4,53	677	6,12	32,59	3,99	2,05	2,78	22,48
3R60F1				57,57	5,14	4,39	5,58	833	7,54	40,12	4,91	2,53	3,42	27,67
****														
<b>Precipitation hardenable steels</b>														
9RU10	1.4568	631	2388	28,09	2,51	2,14	2,72	406	3,68	19,57	2,40	1,23	1,67	13,50
NANOFLEX				56,56	5,05	4,31	5,48	818	7,40	39,41	4,82	2,48	3,36	27,19
1RK95				27,67	2,47	2,11	2,68	400	3,62	19,28	2,36	1,22	1,64	13,30
****														
<b>Duplex stainless steels (austenitic-ferritic)</b>														
SAF2205	EN 1.4462		2377	46,86	4,18	3,58	4,54	678	6,13	32,66	4,00	2,06	2,78	22,53
SAF2507	EN 1.4410		2328	54,58	4,87	4,16	5,29	790	7,14	38,03	4,66	2,40	3,24	26,24
SAF3207HD				54,55	4,87	4,16	5,28	789	7,14	38,01	4,65	2,40	3,24	26,22
****														
<b>Ferritic stainless chromium steel</b>														
1C429				16,15	1,44	1,23	1,56	234	2,11	11,26	1,38	0,71	0,96	7,77
1C44Mo20				21,95	1,96	1,67	2,13	318	2,87	15,29	1,87	0,96	1,30	10,55
0XC34				13,50	1,21	1,03	1,31	195	1,77	9,41	1,15	0,59	0,80	6,49
1C34				13,42	1,20	1,02	1,30	194	1,76	9,35	1,15	0,59	0,80	6,45
****														
<b>Nickel-base alloy</b>														
SANICRO75X2	UNS N07750			153,73	13,72	11,73	14,89	2 224	20,12	107,13	13,11	6,75	9,13	73,90
SAN62TINb				134,20	11,97	10,24	13,00	1 942	17,57	93,51	11,45	5,90	7,97	64,51
****														
<b>Energy surcharge per kg included in total surcharge</b>				2,35	0,21	0,18	0,23	34	0,31	1,63	0,20	0,10	0,14	1,13